

# The Consultative Committee for Space Data Systems Recommended Standard CCSDS 508.0-B-1 TECHNICAL CORRIGENDUM 2

Issue Date: October 2021

## **Conjunction Data Message**

#### **TECHNICAL CORRIGENDUM 2**

The Management Council of the Consultative Committee for Space Data Systems (CCSDS) has authorized the publication of technical corrigendum 2 to CCSDS 508.0-B-1, issued June 2013.

*Page 1-5* 

Update reference [6] with current issue.

Page 4-1, subsection 4.1, change

from:

https://sanaregistry.org/r/ndmxml/ndmxml-1.0-tdm-2.0.xsd

to:

- https://sanaregistry.org/r/ndmxml\_unqualified/ndmxml-2.0.0-cdm-1.0.xsd for messages with elements not qualified with respect to a namespace;
- https://sanaregistry.org/r/ndmxml\_qualified/ndmxml-2.0.0-cdm-1.0.xsd for messages with elements qualified with respect to a namespace.
- NOTE Reference [6] subsection 4.3 has more information regarding messages with elements qualified with respect to a namespace.

Distribution Control Number: TC 21-37 Reference Number: CCSDS 508.0-B-1 Cor. 2

NOTE - Current versions of CCSDS documents are maintained at the CCSDS Web site:

http://www.ccsds.org/

Correspondence regarding CCSDS documents should be addressed to

CCSDS Secretariat
National Aeronautics and Space Administration
Washington, DC, USA
Email: secretariat@mailman.ccsds.org

Page 4-1, subsection 4.1, change

from:

The location of the CDM/XML XSLT converter is http://sanaregistry.org/r/ndmxml/ndmxml-1.0-cdm-1.0.xsl.

to:

The location of the CDM/XML XSLT converter is:

- https://sanaregistry.org/r/ndmxml\_unqualified/ndmxml-2.0.0-cdm-1.1.xsl for messages with elements not qualified with respect to a namespace;
- https://sanaregistry.org/r/ndmxml\_qualified/ndmxml-2.0.0-cdm-1.1.xsl for messages with elements qualified with respect to a namespace.
- NOTE Reference [6] subsection 4.3 has more information regarding messages with elements qualified with respect to a namespace.

Page 4-3, after subsection 4.3.3.2, add

**4.3.3.3** For messages with elements qualified with respect to a namespace, the NDM/XML namespace must next be coded, exactly as shown:

xmlns:ndm="urn:ccsds:schema:ndmxml"

The value that follows the 'xmlns:' in the NDM/XML name space ('ndm' in this case) is a prefix that must be used on every XML tag.

NOTE – This xmlns:ndm setting is only necessary for messages with elements qualified with respect to a namespace, but it does not hurt anything for it to appear on any NDM/XML instantiation.

Page 4-3, subsection 4.3.3.3 (4.3.3.4 after change above), change

from:

xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/ndmxml-1.0-master.xsd"

to:

- xsi:noNamespaceSchemaLocation="https://sanaregistry.org/r/ndmxml\_unqualified/n dmxml-2.0.0-master-2.0.xsd" for messages with elements not qualified with respect to a namespace;
- xsi:noNamespaceSchemaLocation="https://sanaregistry.org/r/ndmxml\_qualified/ndm xml-2.0.0-master-2.0.xsd" for messages with elements qualified with respect to a namespace.

Page 4-4, subsection 4.3.3.8 (4.3.3.9 after change above), change

from:

NOTE – The following example root element tag for a CDM instantiation combines all the directions in the preceding several subsections:

```
<?xml version="1.0" encoding="UTF-8"?>
<cdm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="https://sanaregistry.org/r/ndmxml/ndmx
ml-1.0-master.xsd"
id="CCSDS_CDM_VERS" version="1.0">
```

to:

#### **NOTES**

The following example root element tag for a CDM instantiation combines all the directions in the preceding several subsections for messages with elements not qualified with respect to a namespace:

```
<?xml version="1.0" encoding="UTF-8"?>
<cdm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation=
"https://sanaregistry.org/r/ndmxml_unqualified/ndmxml-2.0.0-master-2.0.xsd"
id="CCSDS_CDM_VERS" version="1.0">
```

The following example root element tag for a CDM instantiation combines all the directions in the preceding several subsections for messages with elements qualified with respect to a namespace:

```
<?xml version="1.0" encoding="UTF-8"?>
<cdm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ndm="urn:ccsds:schema:ndmxml"
xsi:noNamespaceSchemaLocation=
"https://sanaregistry.org/r/ndmxml_qualified/ndmxml-2.0.0-master-2.0.xsd"
id="CCSDS_CDM_VERS" version="1.0">
```

#### Page 4-7, subsection 4.4, change

#### from:

```
<cdm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/n
dmxml-1.0-master.xsd"
id="CCSDS_CDM_VERS" version="1.0">
```

to:

<cdm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ndm="urn:ccsds:schema:ndmxml"
xsi:noNamespaceSchemaLocation="https://sanaregistry.org/r/ndmxml\_
unqualified/ndmxml-2.0.0-master-2.0.xsd" id="CCSDS\_CDM\_VERS"
version="1.0">